

Nozzle Placing Machine with Automatic Packing Device - Mod. MBECC

Automatic nozzle placing machine for nozzles with or without clip, or for both types of nozzles, also equipped with an automatic multi-format packing device.



Machine with a **fully automatic** system **for handling the nozzles**, it can be equipped to work with nozzles **with clip**, or **with two stations** to be able to work with **both types** of nozzles.

This machine is equipped with a **carton moulder** and **fully automatic packing device** for boxing the cartridges with the nozzles inside pre-formed cartons (opened manually by the operator).

- Ramp/slide for the automatic input of the cartridges, to be placed in line at the exit of the automatic filling machine.
- Automatic cartridge loader from the entrance ramp to the double chain for the step-by-step movement
 of the cartridges.
- Station for the insertion of the nozzle with clip on the cartridge, or station for the positioning of the nozzles without clip on the cartridges (or double station for nozzles with clips and without clips in case both solutions are desired).
- Automatic feed of the nozzles, with or without clip, from the hopper to the ground with a capacity
 of about 2000 nozzles.
- Automatic loader of the nozzles from the hopper to the roller selection and orientation system patented by Nannini Renato (very quiet operation), or to a circular vibrating orienting feeder (optional).
- Storage unit of flat cartons to be formed with 30-40 carton capacity.
- Carton forming station with opening of the same in a horizontal position and closing of the rear (or lower) flaps of the carton.



Nozzle Placing Machine with Automatic Packing Device - Mod. MBECC

- Unit for the accumulation of cartridge rows with nozzles to be packed, in accordance to the type of carton used at that time (the machine is multi-size and makes it possible, with simple adjustments, to work with boxes in sizes of 6, 8, 12, 15, 16, 20, 24, 25, 30).
- Pusher for the horizontal placement of the cartridge rows with nozzles inside the box.
- · System for flipping the full box from horizontal to vertical.
- Roller for the ejection of the box towards the possible automatic taping machine to seal the box with tape on top and bottom.
- **Production speed: standard** version up to **50 nozzles/cartridges per minute** depending on the carton format used, and up to **80 nozzles/cartridges per minute** in the **version** with **double** nozzle feeding **stations**.

Nannini Renato Machinery s.r.l.

via Urbania, 26

48018 Faenza RA

• It can be equipped on request with a **cartridge rolling system** to rotate each cartridge during the **ink-jet printing** of the batch number and/or expiry date.



